

**TECHNICAL DETAILS – testo 184 T4**

Temperature - Pt1000	
<b>Measuring range</b>	-80 to +70 °C
<b>Accuracy</b>	±0.8 °C (-80 to -35.1 °C) ±0.5 °C (-35 to +70 °C)
<b>Resolution</b>	0.1 °C
<b>Reaction time</b>	t90 = 30 min
<b>Measuring rate</b>	1 min to 24 h
General technical data	
<b>Weight</b>	44 g
<b>Dimensions</b>	97 x 12 x 40 mm (LxWxH)
<b>Operating temperature</b>	-80 to +70 °C
<b>Product-/housing material</b>	ABS
<b>Protection class</b>	IP67
<b>System requirements</b>	Adobe® Acrobat Reader
<b>Product colour</b>	white



General technical data	
<b>Standards</b>	EN 12830; CE 2014/30/EU; DIN EN 50581:2013; DIN EN 61326-1:2013; 21 CFR Part 11
<b>Certificate type</b>	Certified by HACCP International
<b>Channels</b>	1 internal
<b>Operating time</b>	unlimited
<b>Authorizations</b>	CE; RTCA/DO-160G
<b>Alarm function</b>	by LED
<b>Battery type</b>	Lithium battery TLH-2450, 3V, exchangeable
<b>Battery life</b>	100 days (at 15 mins measurement rate)
<b>Interface</b>	USB; NFC
<b>Memory</b>	40,000 measuring values
<b>Storage temperature</b>	-80 to +70 °C

