



TECHNICAL DETAILS – testo 315-3

Attachable humidity module - Capacitive	
Measuring range	+5 to +95 %RH
Accuracy	±2.5 %RH (5 to +95 %RH)
Resolution	0.1 %RH
Ambient CO ₂	
Measuring range	0 to 10000 ppm
Accuracy	±300 ppm (0 to 4000 ppm) 8 % of mv (4000 to 6000 ppm) 500 ppm (6000 to 10000 ppm)
Resolution	10 ppm
Ambient CO	
Measuring range	0 to 100 ppm
Accuracy	±3 ppm (0 to 20 ppm) ±5 ppm (>20 ppm)
Resolution	0.5 ppm
Temperature	



Temperature	
Measuring range	-10 to +60 °C
Accuracy	±0.5 °C (±1 Digit)
Resolution	0.1 °C
General technical data	
Operating humidity	0 to 95 %RH
Dimensions	190 x 65 x 40 mm
Operating temperature	0 to +40 °C
Protection class	IP40 acc. to EN 60529
Standards	According to EN 50543
EU-/EG-guidelines	2004/108/EG
Interface	IRDA / optional Bluetooth
Storage battery type	Lithium polymer rechargeable battery
Battery charging option	In instrument via mains unit
Battery charge	In instrument via charger



General technical data	
Battery life	10 h measurement time (at +20 °C/+68 °F) / Mains operation possible
Storage temperature	-20 to +60 °C
Weight	200 g

