


TECHNICAL DETAILS – testo 606-2

Temperature - NTC	
Measuring range	-10 to +50 °C
Accuracy	±0.5 °C
Resolution	0.1 °C
Humidity - Capacitive	
Measuring range	0 to 100 %RH
Accuracy	±2.5 %RH (5 to 95 %RH)
Resolution	0.1 %RH

Please see the additional accuracy information for humidity in the instruction manual.

Wood / Building material moisture	
Measuring range	8.8 to 54.8 % by weight; beech, spruce, larch, birch, cherry, walnut 7.0 to 47.9 % by weight; oak, pine, maple, ash-tree, douglas fir, meranti 0.9 to 22.1 % by weight; cement screed, concrete 0.0 to 11.0 % by weight; anhydrite screed 0.7 to 8.6 % by weight; cement mortar 0.6 to 9.9 % by weight; lime mortar, plaster 0.1 to 16.5 % by weight; bricks
Accuracy	±1 %
Resolution	0.1



Wood / Building material moisture	
Measuring rate	1 s
General technical data	
Dimensions	119 x 46 x 25 (incl. protective cap)
Operating temperature	-10 to +50 °C
Protection class	IP20
Battery type	2 AAA micro batteries
Battery life	130 h (average, without display illumination)
Storage temperature	-40 to +70 °C
Weight	90 g (protective cap and batteries included)

